

Product Description

HomeGuard Protectacote Termite and Waterproofing Barrier is an acrylic polymer latex composition with a high loading of inorganic fillers. On curing, it forms a tough, flexible, termite resistant and waterproof film. Bifenthrin is the active ingredient in HomeGuard Protectacote Termite and Waterproofing Barrier. The active ingredient content is such that when these liquid products cure, the resulting barrier has a bifenthrin content of 1g/kg. The active ingredient is uniformly dispersed throughout the product. It both kills and repels termites.

Certificate Holder

FMC Australasia Pty Ltd

ABN 45 095 326 891
Building B, Level 2, 12 Julius Ave
North Ryde NSW 2113.

P: 1800 066 355

W: www.fmcaustralasia.com.au

Certification Body



CertMark International Pty Ltd

T/A CertMark Australia
ABN: 80 111 217 568
JAS-ANZ Accreditation No.
Z4450210AK
PO Box 7144, Sippy Downs Qld 4556
+61 (02) 6100 4300

www.CertMark.org

Certificate of Conformity



This is to certify compliance of

HomeGuard Protectacote Termite and Waterproofing Barrier

Product Purpose, Use and Application

- **a.** When properly installed, the system forms a full and continuous waterproof and termite resistant perimeter barrier that works by forcing termite activity into the open where it can be detected by regular inspection.
- b. Must be installed in accordance with the Installation Manual for HomeGuard Protectacote Termite and Waterproof Barrier Version 1.4 November 2015.
- c. Only to be installed by HomeGuard Protectacote Termite and Waterproofing Barrier accredited installers.
- d. When used as a termite barrier in conjunction with a concrete slab the slab must be designed and constructed according to AS2870:2011 or AS3600:2009 (including amendment 1, as per BCA 2016).
- e. When used as a termite barrier in masonry walls, the mortar joint under the barrier shall be full (have no gaps or porosity to provide an inspection zone).

Complies with the National Construction Code – Building Code of Australia 2016 Volume One Volume Two

- dispersed throughout the product. It both kills and repels termites.

 a. Clause A0.2 (c) being a combination of compliance with the Deemed-to-Satisfy Provisions and formulating a Performance Solution which complies with the Performance Requirements.
 - b. BP1.1 (a) and (b) (xv) for termite management system
 - BP1.2 for termite management system, including QLD State Variations
 - d. B1.4 (i) Termite Risk Management (including QLD State Variation).
- a. Clause 1.0.2 (c) being a combination of compliance with the Deemed-to-Satisfy Provisions and formulating a Performance Solution which complies with the Performance Requirements.
- P2.1.1 (a), (b) (xv) and (c) for termite management system, including QLD State Variations.
 - i. 3.1.3.1 Application (including QLD State Variation).
 - ii. 3.1.3.2 Requirements for termite management systems (including QLD State Variation).
 - 3.1.3.3 Termite management systems (including QLD State Variation).
 - iv. 3.1.3.4 Durable notice (including QLD State Variation).

Conditions and Limitations

- This certificate is limited to the details within this certificate, including the compliance elements, product description and purpose or use. This certification is to be read, considered used as a whole document and reproduced in its entirety.
- In accordance with BCA Volume One 2016: B1.4 (i), (i) & (ii), including NT & QLD state & territory variations, and BCA Volume Two 2016: Part 3.1.3.2 (b), including QLD state variations, a durable notice must be permanently fixed to the building in a prominent location, such as a meter box or the like indicating:
- The method of termite risk management; and
- The date of installation of the systems; and
- The installers or manufacturers recommendations for the scope and frequency of future inspections for termite activity.
- Inspections must be undertaken annually in accordance with the above installation manuals to determine that no bridging or breaching of the termite management system has occurred.
- Compliance with AS 3660.1:2000 is valid until 30 April 2017 when the transitional period expires.
- This Certificate excludes compliance of the product in relation to dampproofing.

ABCB Disclaimer

- This Certificate of Conformity is issued by an accredited certification body under arrangement with JAS-ANZ. The ABCB does not in any way warrant, guarantee or represent that the Product the subject of this Certificate of Conformity conforms to the BCA, nor accepts any liability arising out of the use of the Product. The ABCB disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, www.abcb.gov.au.

John Thorne Livi Krovatin

19/05/2016 Date of Issue 19/05/2019 Date of Expiry CMA-CM40156-I01-R01 Certificate Number

CertMark International

Unrestricted Building Certifier