

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : BIFLEX® ULTRA-LO-ODOUR

Other means of identification : BIFLEX ULTRA
BIFENTHRIN 100 G/L EC

Recommended use of the chemical and restrictions on use

Recommended use : Termiticide and insecticide

Restrictions on use : Use as recommended by the label.

Manufacturer or supplier's details

Company : FMC Australasia Pty Ltd

Address : Building B, Level 2, 12 Julius Avenue,
North Ryde NSW 2113
Australia

Telephone : 1800 066 355

Telefax : (02) 9923 6011

E-mail address : SDS-Info@fmc.com

Emergency telephone number : For leak, fire, spill or accident emergencies, call:
1800 033 111 (Ixon)

Medical emergency:
1 800 033 111 (Transport and 24 h Medical information)

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 4

Serious eye damage/eye irritation : Category 1

Skin sensitisation : Category 1

Specific target organ toxicity - single exposure : Category 1 (Central nervous system)

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H302 + H332 Harmful if swallowed or if inhaled.
H304 May be fatal if swallowed and enters airways.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H370 Causes damage to organs (Central nervous system).
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Very toxic to aquatic life with long lasting effects.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
bifenthrin (ISO)	82657-04-3	>= 10 -< 20
Alcohols, C12-14. ethoxylated	68439-50-9	>= 10 -< 30
Distillates (petroleum), hydrotreated middle; Gasoil — unspecified	64742-46-7	>= 60 -<= 80
Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts	90194-26-6	>= 1 -< 3

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

Most important symptoms and effects, both acute and delayed : Harmful if swallowed or if inhaled.
May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Causes serious eye damage.
Causes damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
Foam

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Thermal decomposition can lead to release of irritating gases and vapours.
Halogenated compounds
Carbon oxides

Specific extinguishing methods : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Hazchem Code : •3Z

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.
-

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Personal protective equipment

- Respiratory protection : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
- Hand protection
Material : Wear chemical resistant gloves, such as barrier laminate, butyl rubber or nitrile rubber.
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and con-

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

centration of the dangerous substance at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow-orange

Odour : aromatic, hydrocarbon-like

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : not determined

Flash point : 94 °C

Self-ignition : not determined

Density : ca. 0.9 g/cm³

Solubility(ies)
Water solubility : emulsifiable

Partition coefficient: n-octanol/water : Not applicable

Viscosity
Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : The product is not oxidizing.

Metal corrosion rate : Not corrosive to metals

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

Incompatible materials : Strong oxidizing agents
Strong acids
Strong bases

Hazardous decomposition products : Stable under recommended storage conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed or if inhaled.

Product:

Acute oral toxicity : LD50 (Rat, male and female): 531 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 4.94 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Components:

bifenthrin (ISO):

Acute oral toxicity : LD50 (Rat, male and female): 50.2 - 58.8 mg/kg
Symptoms: Convulsions, Tremors

Acute inhalation toxicity : LC50 (Rat, female): 0.6 - 1.2 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Symptoms: Tremors, Convulsions

LC50 (Rat, male): 1.10 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Symptoms: Tremors, Fatality

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Remarks: no mortality

Alcohols, C12-14. ethoxylated:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 1.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,000 mg/kg
Method: OECD Test Guideline 402

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Acute oral toxicity : LD50 (Rat, male and female): 1,080 - 1,630 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Species : Rabbit
Result : No skin irritation

Remarks : Extremely corrosive and destructive to tissue.

Components:**bifenthrin (ISO):**

Species : Rabbit
Result : slight or no skin irritation.
GLP : yes

Species : Rabbit
Method : OECD Test Guideline 404
Result : slight or no skin irritation.
GLP : yes

Alcohols, C12-14. ethoxylated:

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Species : reconstructed human epidermis (RhE)
Method : OECD Test Guideline 439
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Species : Rabbit
Result : Irreversible effects on the eye
Remarks : May cause irreversible eye damage.

Components:

bifenthrin (ISO):

Species : Rabbit
Result : Slight or no eye irritation
Method : OECD Test Guideline 405
GLP : yes

Alcohols, C12-14. ethoxylated:

Species : Rabbit
Result : Irreversible effects on the eye
Method : OECD Test Guideline 405

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Species : Bovine cornea
Result : Irreversible effects on the eye
Method : OECD Test Guideline 437
Remarks : Based on data from similar materials

BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

Respiratory or skin sensitisation**Skin sensitisation**

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Species	:	Guinea pig
Result	:	May cause sensitisation by skin contact.
Remarks	:	Causes sensitisation.

Components:**bifenthrin (ISO):**

Test Type	:	Maximisation Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	May cause sensitisation by skin contact.
GLP	:	yes

Alcohols, C12-14. ethoxylated:

Exposure routes	:	Skin contact
Species	:	Guinea pig
Method	:	Directive 67/548/EEC, Annex V, B.6.
Result	:	Does not cause skin sensitisation.

Exposure routes	:	Skin contact
Species	:	Humans
Result	:	Does not cause skin sensitisation.

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Test Type	:	Buehler Test
Exposure routes	:	Skin contact
Species	:	Guinea pig
Result	:	Does not cause skin sensitisation.
Remarks	:	Based on data from similar materials

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.
Remarks	:	Based on data from similar materials

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

Components:**bifenthrin (ISO):**

Genotoxicity in vitro : Test Type: gene mutation test
 Test system: Chinese hamster ovary cells
 Metabolic activation: with and without metabolic activation
 Result: negative

Test Type: reverse mutation assay
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Test Type: Mouse lymphoma assay
 Metabolic activation: with and without metabolic activation
 Result: negative

Genotoxicity in vivo : Test Type: Sex-linked Recessive Lethal Test
 Species: Drosophila melanogaster (vinegar fly)
 Result: negative

Test Type: unscheduled DNA synthesis assay
 Species: Rat
 Method: OECD Test Guideline 486
 Result: negative

Alcohols, C12-14. ethoxylated:

Genotoxicity in vitro : Test Type: reverse mutation assay
 Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 471
 Result: negative

Metabolic activation: with and without metabolic activation
 Method: OECD Test Guideline 473
 Result: negative

Genotoxicity in vivo : Application Route: Intraperitoneal injection
 Method: OECD Test Guideline 474
 Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Genotoxicity in vitro : Test Type: reverse mutation assay
 Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)
 Result: negative

Genotoxicity in vivo : Test Type: Bone marrow chromosome aberration
 Species: Rat (male and female)
 Application Route: Intraperitoneal injection
 Result: negative

BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

- Genotoxicity in vitro : Test Type: reverse mutation assay
Result: negative
Remarks: Based on data from similar materials
- Genotoxicity in vivo : Test Type: Bone marrow chromosome aberration
Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 475
Result: negative
Remarks: Based on data from similar materials
- Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:**bifenthrin (ISO):**

- Species : Rat, female
Application Route : Oral
Exposure time : 2 Years
NOAEL : 3 mg/kg bw/day
Result : negative
- Species : Mouse, male
Application Route : Oral
Exposure time : 18 month(s)
NOAEL : 7.6 mg/kg bw/day
Result : positive
Symptoms : malignant tumors

Alcohols, C12-14. ethoxylated:

- Species : Rat, male and female
Exposure time : 24 month(s)
Result : negative

Reproductive toxicity

Not classified based on available information.

Components:**bifenthrin (ISO):**

- Effects on fertility : Test Type: Two-generation study
Species: Rat
Application Route: Oral
General Toxicity - Parent: NOAEL: 3 mg/kg bw/day
General Toxicity F1: NOAEL: 5 mg/kg bw/day
Result: negative
- Effects on foetal develop- : Test Type: Embryo-foetal development

BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

ment

Species: Rabbit
 Application Route: Oral
 General Toxicity Maternal: NOAEL: 2.7 mg/kg bw/day
 Teratogenicity: NOAEL: 2.7 mg/kg bw/day
 Symptoms: Maternal effects
 Result: No teratogenic effects

Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Oral
 General Toxicity Maternal: NOAEL: 1 mg/kg bw/day
 Teratogenicity: NOAEL: 2 mg/kg bw/day
 Result: No teratogenic effects

Species: Rat
 Application Route: Oral
 General Toxicity Maternal: LOAEL: 7.2 mg/kg bw/day
 Developmental Toxicity: LOAEL: 7.2 mg/kg bw/day
 Embryo-foetal toxicity: NOEL: 9.0 mg/kg bw/day
 Method: OECD Test Guideline 426
 Result: Animal testing did not show any effects on fertility.,
 Some evidence of adverse effects on development, based on
 animal experiments.

Alcohols, C12-14. ethoxylated:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Effects on fertility : Test Type: Two-generation study
 Species: Rat
 Application Route: Oral
 General Toxicity F1: NOAEL: 1,000 mg/kg body weight
 Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Dermal
 General Toxicity Maternal: LOAEL: 50 mg/kg body weight
 Developmental Toxicity: NOAEL: 50 mg/kg body weight
 Remarks: Developmental effects are a consequence of maternal toxicity.
 Based on data from similar materials

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Effects on fertility : Test Type: Two-generation study
 General Toxicity - Parent: NOAEL: > 350 mg/kg body weight
 General Toxicity F1: NOAEL: > 350 mg/kg body weight
 Method: OECD Test Guideline 416
 Result: negative
 Remarks: Based on data from similar materials

Effects on foetal development : Test Type: reproductive and developmental toxicity study

BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

ment

Species: Rat
 Developmental Toxicity: NOAEL: > 350 mg/kg body weight
 Result: negative
 Remarks: Based on data from similar materials

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

STOT - single exposure

Not classified based on available information.

Components:**bifenthrin (ISO):**

Target Organs : Central nervous system
 Assessment : Causes damage to organs.

STOT - repeated exposure

Causes damage to organs (Nervous system) through prolonged or repeated exposure.

Components:**bifenthrin (ISO):**

Target Organs : Central nervous system
 Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Alcohols, C12-14. ethoxylated:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity**Components:****bifenthrin (ISO):**

Species : Rat, male and female
 NOEL : 100 ppm
 Application Route : Oral - feed
 Exposure time : 90 d
 Remarks : No toxicologically significant effects were found.

Species : Dog, male and female
 NOEL : 2.5 mg/kg bw/day
 Application Route : Oral - feed
 Exposure time : 13 w
 Symptoms : Tremors

BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

Alcohols, C12-14. ethoxylated:

Species	:	Rat, male and female
NOAEL	:	110 mg/kg
Application Route	:	Oral
Exposure time	:	2160 h

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Species	:	Rat
NOAEL	:	>= 1.71 mg/l
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	13 weeks
Remarks	:	Based on data from similar materials

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Species	:	Rat, male and female
NOAEL	:	85 mg/kg
LOAEL	:	145 mg/kg
Application Route	:	Oral
Exposure time	:	9 months
Target Organs	:	Kidney, Liver
Remarks	:	Based on data from similar materials

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**bifenthrin (ISO):**

The substance does not have properties associated with aspiration hazard potential.

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks : Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****bifenthrin (ISO):**

Toxicity to fish	:	LC50 (Salmo gairdneri): 0.00015 mg/l Exposure time: 96 h Test Type: flow-through test
------------------	---	---

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

- LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.00035 mg/l
Exposure time: 96 h
Test Type: flow-through test
- LC50 (Oncorhynchus mykiss (rainbow trout)): 0.000256 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes
- LC50 (Pimephales promelas (fathead minnow)): 0.000234 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 0.00011 mg/l
Exposure time: 48 h
- LC50 (Daphnia (water flea)): 0.0016 mg/l
Exposure time: 48 h
- Toxicity to algae/aquatic plants : EC50 (algae): 0.822 mg/l
Exposure time: 72 h
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.00012 mg/l
Exposure time: 21 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.0013 µg/l
Exposure time: 21 d
- NOEC (Daphnia magna (Water flea)): 0.00095 µg/l
Exposure time: 21 d
- Toxicity to soil dwelling organisms : LD50 (Eisenia fetida (earthworms)): > 16 mg/kg
Exposure time: 14 d
- Toxicity to terrestrial organisms : LD50 (Colinus virginianus (Bobwhite quail)): 1,800 mg/kg
- LD50 (Anas platyrhynchos (Mallard duck)): > 2,150 mg/kg
- LD50 (Apis mellifera (bees)): 0.1 - 0.35 µg/bee
Exposure time: 24 h
End point: Acute oral toxicity
Method: OECD Test Guideline 213
- LD50 (Apis mellifera (bees)): 0.1 - 0.3 µg/bee
Exposure time: 24 h
End point: Acute contact toxicity
Method: OECD Test Guideline 214

Alcohols, C12-14. ethoxylated:

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.1 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.7 mg/l
Exposure time: 48 h
Test Type: static test
Method: Directive 67/548/EEC, Annex V, C.2.
- Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 0.87 mg/l
Exposure time: 72 h
Test Type: static test
- Toxicity to fish (Chronic toxicity) : EC10 (Pimephales promelas (fathead minnow)): 0.96 mg/l
Exposure time: 30 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10 (Daphnia magna (Water flea)): 0.53 mg/l
Exposure time: 21 d
- Toxicity to microorganisms : EC50 (Pseudomonas putida): 1,000 g/l
Exposure time: 3 h
- Toxicity to soil dwelling organisms : NOEC (Eisenia fetida (earthworms)): 220 mg/kg
Method: OECD Test Guideline 222
- Plant toxicity : NOEC: \geq 100 mg/l
Exposure time: 456 h

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

- Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 24 h
Test Type: semi-static test
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 10 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
- Toxicity to microorganisms : EL50 (Tetrahymena pyriformis): > 1,000 mg/l
Exposure time: 40 h
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

- Toxicity to fish : LC50 : 1.7 - 7.7 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 5.7 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: water accommodated fractions (WAF)
Based on data from similar materials
- Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 10 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: water accommodated fractions (WAF)
Based on data from similar materials
- EL50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: water accommodated fractions (WAF)
Based on data from similar materials
- Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 0.23 mg/l
Exposure time: 72 d
Test Type: flow-through test
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 1.18 mg/l
Exposure time: 21 d
Test Type: flow-through test
- Toxicity to microorganisms : EC50 (activated sludge): 162 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Based on data from similar materials

Persistence and degradability**Components:****bifenthrin (ISO):**

Biodegradability : Result: Not readily biodegradable.

Alcohols, C12-14. ethoxylated:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Biodegradability : Result: Readily biodegradable.

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

Biodegradation: > 60 %

Exposure time: 28 d

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

bifenthrin (ISO):

Bioaccumulation : Species: Lepomis macrochirus (Bluegill sunfish)
Bioconcentration factor (BCF): 1,709
Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is possible.
See section 9 for octanol-water partition coefficient.

Partition coefficient: n-octanol/water : log Pow: 6

Alcohols, C12-14. ethoxylated:

Bioaccumulation : Bioconcentration factor (BCF): < 800
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 5.12 - 5.32 (25 °C)

Distillates (petroleum), hydrotreated middle; Gasoil — unspecified:

Partition coefficient: n-octanol/water : log Pow: > 4

Benzenesulfonic acid, 4-C10-14-alkyl derivs., calcium salts:

Partition coefficient: n-octanol/water : log Pow: 4.3 - 5.8 (25 °C)
pH: 7
Method: OECD Test Guideline 117

Mobility in soil

Components:

bifenthrin (ISO):

Distribution among environmental compartments : Koc: 236610 ml/g, log Koc: 5.37
Remarks: immobile

Alcohols, C12-14. ethoxylated:

Distribution among environmental compartments : Koc: > 4656 ml/g, log Koc: > 3.7
Remarks: Low mobility in soil

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Bifenthrin)
Class : 9
Packing group : III
Labels : 9

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Bifenthrin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964
Environmentally hazardous : yes

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Bifenthrin)
Class : 9
Packing group : III

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

Labels	:	9
EmS Code	:	F-A, S-F
Marine pollutant	:	yes
Remarks	:	Environmentally hazardous substances/Marine Pollutants in single or combination packaging containing a net quantity per single or inner packaging of 5 kg or less for solids, or having a net quantity per single or inner packaging of 5 L or less for liquids may be transported as non-dangerous goods as provided in special provision A197 of the IATA and section 2.10.2.7 of IMDG code.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number	:	UN 3082
Proper shipping name	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bifenthrin)
Class	:	9
Packing group	:	III
Labels	:	9
Hazchem Code	:	•3Z
Remarks	:	Environmentally hazardous substances meeting the descriptions of UN 3077 or UN 3082 are not subject to the ADG Code when transported by road or rail in packagings that do not incorporate a receptacle exceeding 500 kg / liters, or IBCs

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons	:	Schedule 6
--	---	------------

APVMA number: 59269

Prohibition/Licensing Requirements	:	There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regula-
------------------------------------	---	--

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version 1.2 Revision Date: 25.05.2023 SDS Number: 50001561 Date of last issue: 31.07.2021
Date of first issue: 30.07.2021

tions.

The components of this product are reported in the following inventories:

TCSI	:	Not in compliance with the inventory
TSCA	:	Product contains substance(s) not listed on TSCA inventory.
AiIC	:	Not in compliance with the inventory
DSL	:	This product contains the following components that are not on the Canadian DSL nor NDSL. 2-METHYLBIPHENYL-3-YLMETHYL (Z)-(1RS,3RS)-3-(2-CHLORO-3,3,3-TRIFLUOROPROP-1-ENYL)-2,2-DIMETHYLCYCLOPROPANECARBOXYLATE Fatty acid di-ester
ENCS	:	Not in compliance with the inventory
ISHL	:	Not in compliance with the inventory
KECI	:	Not in compliance with the inventory
PICCS	:	Not in compliance with the inventory
IECSC	:	Not in compliance with the inventory
NZIoC	:	Not in compliance with the inventory

SECTION 16. OTHER INFORMATION

Revision Date : 25.05.2023
Date format : dd.mm.yyyy

Full text of other abbreviations

AiIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Con-

SAFETY DATA SHEET



BIFLEX® ULTRA-LO-ODOUR

Version	Revision Date:	SDS Number:	Date of last issue: 31.07.2021
1.2	25.05.2023	50001561	Date of first issue: 30.07.2021

centration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to ensure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

AU / 6N